

JUN 19 2006

Serial No. 10/670,594, filed 9/25/03

**AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions and listings of claims in the application:

**Listing of Claims:**

1. (Previously Presented) A brake slack adjuster comprising:  
  
a housing having an opening with a gear disposed within said opening, said housing including a bore adjacent to said opening;  
  
a worm defining an axis, and disposed within said bore engaging said gear, said worm having an end portion with helical teeth;  
  
an actuator including an outer surface adjacent to said bore and an inner surface having complementary helical teeth engaging said helical teeth of said worm, said actuator having an aperture, and said actuator movable along said axis relative to said worm;  
  
an actuator rod having an end disposed within said aperture, and captured in said actuator by a retainer; and  
  
a pawl assembly coacting with said actuator for retaining said actuator in a rotational position relative to said axis.
2. (Original) The brake slack adjuster according to claim 1, wherein said actuator is plastic.
3. (Original) The brake slack adjuster according to claim 1, wherein said inner and outer surfaces are defined by an arcuate wall.

Serial No. 10/670,594, filed 9/25/03

## 4. (Currently Amended) A brake slack adjuster comprising:

a housing having an opening with a gear disposed within said opening, said housing including a bore adjacent to said opening;

a worm defining an axis, and disposed within said bore engaging said gear, said worm having an end portion with helical teeth;

an actuator including an outer surface adjacent to said bore and an inner surface having complementary helical teeth engaging said helical teeth of said worm, said actuator having an aperture, and said actuator movable along said axis relative to said worm, wherein said inner and outer surfaces are defined by an arcuate wall;

an actuator rod having an end disposed within said aperture, and captured in said actuator by a retainer;

a pawl assembly coacting with said actuator for retaining said actuator in a rotational position relative to said axis; and

a biasing member arranged between said actuator and said ~~housing-bore~~, urging said actuator into engagement with said ~~worm~~ end portion of said worm.

5. (Previously Presented) The brake slack adjuster according to claim 4, wherein said actuator is movable along said axis between non-adjustment and adjustment positions in response to said actuator rod moving between brake apply and brake release positions.

Serial No. 10/670,594, filed 9/25/03

6. (Original) The brake slack adjuster according to claim 5, wherein said biasing member urges said actuator from said adjustment position to said non-adjustment position.

7. (Currently Amended) The brake slack adjuster according to claim 5, wherein said ~~worm~~ helical teeth of said worm and said ~~actuator~~ complementary helical teeth of said actuator temporarily disengage in said adjustment position in response to movement of said actuator rod in a first direction.

8. (Original) The brake slack adjuster according to claim 7, wherein said worm rotates said gear to a desired slack adjuster position in response to movement of said actuator rod in a second direction opposite said first direction.

9. (Original) The brake slack adjuster according to claim 7, wherein said adjustment position corresponds to said brake apply position and said non-adjustment position corresponds to said brake release position.

10. (Previously Presented) The brake slack adjuster according to claim 5, wherein said actuator rod end includes a slot having opposing terminal ends defining said non-adjustment and adjustment positions, and said retainer defined by a pin disposed within said slot and secured to said actuator.

Serial No. 10/670,594, filed 9/25/03

11. (Previously Presented) The brake slack adjuster according to claim 5, wherein said actuator includes a cavity having a length with one end of said length defining said non-adjustment position and the other end of said length defining said adjustment position.

12. (Currently Amended) The brake slack adjuster according to claim 11, wherein ~~said actuator rod~~ end of said actuator rod includes an annular groove, and said retainer defined by a clip received in said annular groove.

13. (Original) The brake slack adjuster according to claim 11, wherein said actuator includes a flange having said aperture and defining said one end.

Serial No. 10/670,594, filed 9/25/03

14. (Currently Amended) A brake slack adjuster comprising:
- a housing having an opening with a gear disposed within said opening, said housing including a bore adjacent to said opening;
  - a worm defining an axis, and disposed within said bore engaging said gear, said worm having an end portion with helical teeth;
  - an actuator including an outer surface adjacent to said bore and an inner surface having complementary helical teeth engaging said helical teeth of said worm, said actuator movable along said axis relative to said worm;
  - a biasing member between said actuator and said ~~housing-bore~~ urging said actuator into engagement with said ~~worm~~ end portion of said worm; and
  - a pawl assembly coacting with said actuator for preventing ~~rotation~~ rotational movement of said actuator about said axis relative to said housing.

15. (Previously Presented) The brake slack adjuster according to claim 14, wherein said pawl assembly is received within a second bore in said housing formed transverse to said bore, said pawl assembly having an end captured within an elongated slot in said actuator which is generally parallel with said axis.

16. (Previously Presented) The brake slack adjuster according to claim 15, wherein said pawl assembly includes a neck adjacent to said end, and said elongated slot defines a lip with said lip received by said neck.

Serial No. 10/670,594, filed 9/25/03

17. (Previously Presented) The brake slack adjuster according to claim 16, wherein said elongated slot includes an enlarged opening for receiving said end, and said elongated slot excluding said enlarged opening includes a width less than an end diameter.

18. (Cancelled)

19. (Previously Presented) The brake slack adjuster according to claim 2, wherein a plastic biasing member is provided by said actuator.

20. (Cancelled)